

. LAYER FOR DRAINAGE AND WATER STORAGE

Supply and installation of:

DAKU FSD 20 components, which are rigid sheets made of sintered expanded polystyrene foam. They are produced with materials free from regenerated elements. They are of white color, barely flammable and their raw mass is of 25 kg/m³. They are provided with CE marking and comply with UNI EN 13163 standards. **All DAKU FSD 20 components comply with UNI 11235:2015 standards.** They perform a threefold function of mechanical protection of the waterproof surface, water drainage and water storage.

Technical data:

- Dimensions	1000 x 1250 mm	
- Thickness	82 mm	
- Raw mass	25 Kg/m ³ (+/-10%)	
- Maximum water storage capacity	13,1 liters/m²	
- Gap between water and filter	10 mm	
- Free air volume at maximum water storage capacity	21,5 liters/m ²	
- Drainage capacity at 20 kPa with i=0.01		
vertical	1,46 l/ms	(EN ISO 12958)
horizontal	1,44 l/ms	(EN ISO 12958)
- Drainage capacity at 20 kPa with i=0.1		
vertical	4,95 l/ms	(EN ISO 12958)
horizontal	4,90 l/ms	(EN ISO 12958)
- Vertical drainage capacity	0,73 l/mqs	(EN ISO 11058)
- Thermal dispersion resistance	0,71 mq x K/W	
- Thermal conductivity	0,034 W/mK	(UNI EN 12667)
- Height of support feet	20 mm	
- Number of support feet	252 pz	
- Surface	2.052 cmq/mq	
- Flammability Class	E	(EN 13051)

The installation of the DAKU FSD 20 components is made directly on the insulation/waterproof surface or, when necessary or agreed, on the DAKU FLT filling layers.

m² 0.00



Daku Italia s.r.l.

Sede legale ed amministrativa

Via XIII Martiri, 28
30027 San Donà di Piave (VE) - Italy
Tel: +39 0421 51864
Fax: +39 0421 334491

Sedi commerciali

Piazzale della Pieve, 16
47121 Forlì (FC) - Italy
Tel: +39 0543 480496
Fax: +39 0543 487642

Strada per Castelnuovo Nigra, 84
10081 Castellamonte (TO) - Italy
Tel: +39 344 3415605

www.daku.it
daku@daku.it
P.I. / C.F. 02972700278
REA. N. VE 270000

