

## . FILLING LAYER

### Supply and installation of:

**DAKU FLT 300** which is a white non-woven fabric geotextile made of highly tenacious polypropylene. The fabric is treated with UV rays, needled, calendered, glue-free, rot-proof, resistant to micro-organisms and without recycled materials. It is used as a filling layer and as a protection layer on the waterproof surface wherever some extra protection is needed or to reduce the outflow coefficient of the coverings.

### Technical features:

- Roll dimensions:	2,00 x 50 m (100 mq)	
- <b>Areal mass density:</b>	<b>300 gr/mq (+/-10%)</b>	<b>(EN ISO 9864)</b>
- Thickness at 2kPa:	1,60 mm (+/-20%)	(EN ISO 9863-1)
- Tensile strength:		
Vertical	2,5 Kn/m (-10%)	(EN ISO 10319)
Horizontal	2,7 Kn/m (-10%)	(EN ISO 10319)
- Elongation at break:		
Vertical	50% (+/-30%)	(EN ISO 10319)
Horizontal	60% (+/-30%)	(EN ISO 10319)
- Resistance to static punching:	0,60 kN (-10%)	(EN ISO 12236)
- Resistance do dynamic punching:	40 mm (+20%)	(EN ISO 13433)
- Speed rating:	60 mm/s (-30%)	(EN ISO 11058)
- Horizontal flow capacity:	2.7x10 <sup>-3</sup> l/ms (-30%)	(EN ISO 12958)
- Pores openness:	0,055 mm (+/-30%)	(EN ISO 12956)
- Resistance to oxidation:	minimum 25 years	(EN ISO 12956)

DAKU FLT geotextiles are installed directly on the insulation/waterproof surface, overlapping the sheets for 10 cm and folding them on the vertical edges of the surfaces for a height equal to the one of the DAKU FSD/DAKU DRAIN components or of the paved surface/protection blocks.

**M2 approx. 0.00**



Daku Italia s.r.l.

Sede legale ed amministrativa

Via XIII Martiri, 28  
30027 San Donà di Piave (VE) - Italy  
Tel: +39 0421 51864  
Fax: +39 0421 334491

Sedi commerciali

Piazzale della Pieve, 16  
47121 Forlì (FC) - Italy  
Tel: +39 0543 480496  
Fax: +39 0543 487642

Strada per Castelnuovo Nigra, 84  
10081 Castellamonte (TO) - Italy  
Tel: +39 344 3415605

[www.daku.it](http://www.daku.it)  
daku@daku.it  
P.I. / C.F. 02972700278  
REA. N. VE 270000

