

## . CONTAINMENT/SEPARATION COMPONENT

### Supply and installation of:

**DAKU PRO**, which is a containment component 8 cm high. It is used for the containment of the DAKU ROOF SOIL substrate or of other components (fillers, blocks, paving) in DAKU's systems. It is built in an aluminum-magnesium alloy (pressed and folded) with good resistance to corrosion and traction. It has holes for drainage and ventilation (4 mm wide) in compliance with the UNI 11235/2015 standards.

Technical data:

#### **...ml of DAKU PRO 80 - AL**

- Thickness	2,0 mm
- Wideness	144 mm
- Length	2,00 ml
- Drainage and ventilation surface	144 cmq/ml

#### **...ml of DAKU PRO FLEX 80 - AL**

- Thickness	2,0 mm
- Wideness	144 mm
- Length	2,00 ml
- Drainage and ventilation surface	144 cmq/ml

#### **n° .... pcs of DAKU GL80 – AL** rectilinear joint

#### **n° .... pcs of DAKU GA80 – AL** angular joint

The components are installed directly on the DAKU STABILFILTER substrates without using nails or bolts. The connections between the components will be locked with the DAKU GL80 internal joints and with the DAKU GA80 special angular joints.

**ml 0,00**



Daku Italia s.r.l.

Sede legale ed amministrativa

Via XIII Martiri, 28  
30027 San Donà di Piave (VE) - Italy  
Tel: +39 0421 51864  
Fax: +39 0421 334491

Sedi commerciali

Piazzale della Pieve, 16  
47121 Forlì (FC) - Italy  
Tel: +39 0543 480496  
Fax: +39 0543 487642

Strada per Castelnuovo Nigra, 84  
10081 Castellamonte (TO) - Italy  
Tel: +39 344 3415605

[www.daku.it](http://www.daku.it)

daku@daku.it  
P.I. / C.F. 02972700278  
REA. N. VE 270000

