

. CONTAINMENT/SEPARATION COMPONENT

Supply and installation of:

DAKU PRO, which is a containment component 17 cm high. It is used for the containment of the DAKU ROOF SOIL substrate or of other components (fillers, blocks, paving) in DAKU's systems. It is built in an aluminum-magnesium alloy (pressed and folded) with good resistance to corrosion and traction. It has holes for drainage and ventilation (4 mm wide) in compliance with the UNI 11235/2015 standards.

Technical data:

...ml of **DAKU PRO 170 MBP - AL**

- Thickness	2,0 mm
- Wideness	327 mm
- Length	2,00 ml
- Drainage and ventilation surface	164,50 cmq/ml

n° pcs of **DAKU GL170 MBP – AL** rectilinear joint

n° pcs of **DAKU GA170 MBP – AL** angular joint

The components are installed directly on the bituminous waterproof surface without using nails or bolts. The components have a stripe of waterproof material attached to the bottom side which is then welded on the waterproof surface of the roof. The connections between the components will be locked with the DAKU GL170 MBP internal joints and with the DAKU GA170 MBP special angular joints.

ml 0,00



Daku Italia s.r.l.

Sede legale ed amministrativa

Via XIII Martiri, 28
30027 San Donà di Piave (VE) - Italy
Tel: +39 0421 51864
Fax: +39 0421 334491

Sedi commerciali

Piazzale della Pieve, 16
47121 Forlì (FC) - Italy
Tel: +39 0543 480496
Fax: +39 0543 487642

Strada per Castelnuovo Nigra, 84
10081 Castellamonte (TO) - Italy
Tel: +39 344 3415605

www.daku.it
daku@daku.it
P.I. / C.F. 02972700278
REA. N. VE 270000

